# **MATERIAL SAFETY DATA SHEET**



1. Product and Company Identification			
Product number 846-001			
Product name	Wood Cleaner		
Effective date	23-Sep-2009		
Company information	Claire Manufacturing Co. 500 Vista Ave. Addison, IL 60101 United States		
Company phone	General Assistance 630-543-7600		
Emergency telephone US	800-424-9300		
Emergency telephone outside US			
Version #	05		
Supersedes date	16-Jan-2009		
	2. Hazards Identification		
Emergency overview	FLAMMABLE CONTENTS UNDER PRESSURE. Aerosol. Will be easily ignited by heat, spark or flames. Irritating to eyes. Prolonged exposure may cause chronic effects.		
Potential health effects			
Routes of exposure	Ingestion. Skin contact.		
Eyes	Causes eye irritation.		
Skin	Prolonged or repeated contact can result in defatting and drying of the skin which ma result in skin irritation and dermatitis (rash).		
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.		
Ingestion	Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.		
Target organs	Central nervous system. Lungs.		
Chronic effects	May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.		
	Discomfort in the chest. Narcosis. Defatting of the skin. Irritation.		

Components	CAS #	Percent
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	15 - 20
n-Butane	106-97-8	10 - 15
Odorless Mineral Spirits	64742-48-9	8 - 10
Propane	74-98-6	5 - 8
Non-hazardous and other components below reportable levels		40 - 60

## 4. First Aid Measures

#### First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.
Skin contact	Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.
Inhalation	Move to fresh air. If symptoms persist, get medical attention.

If material is ingested, immediately contact a poison control center. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures		
Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.	
Extinguishing media		
Suitable extinguishing media	Foam. Dry chemical. Carbon dioxide (CO2). Do not use water jet.	
Protection of firefighters		
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.	
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.	
	6. Accidental Release Measures	
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.	
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.	
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.	
	7. Handling and Storage	
Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.	
Storage	Level 2 Aerosol. Level 1 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.	
	8. Exposure Controls / Personal Protection	

Components	CAS #	TWA	STEL	Ceiling
•				5
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
OSHA				
Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

### Personal protective equipment

Eye / face protection Wear chemical goggles.

**Respiratory protection** 

Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

#### 9. Physical & Chemical Properties

	14. Transport Information			
Waste codes Disposal instructions	D001: Waste Flammable material with a flash point <140 F Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.			
	13. Disposal Considerations			
	LC50 258 mg/L estimated, Fish, 96.00 Hours, EC50 7734 mg/L estimated, Daphnia, 48.00 Hours,			
Ecotoxicity	Components of this product have been identified as having potential environmental concerns.			
	12. Ecological Information			
Teratogenicity	Not expected to be hazardous by OSHA criteria.			
Sensitization	Not expected to be hazardous by OSHA criteria.			
Acute effects	Acute LD50: 8188 mg/kg estimated, Rat, Dermal			
	11. Toxicological Information			
azardous decomposition products No hazardous decomposition products are known.				
Conditions to avoid	Heat, flames and sparks.			
hemical stability	Risk of ignition.			
	10. Chemical Stability & Reactivity Information			
Specific gravity     0.8063 estimated				
Solubility Negligible				
Pressure	50 - 70 psig @ 70F			
Physical state	Liquid.			
оН	7.38 - 8.38			
Form Aerosol.   Odor fruity				
Flash point	-156 °F (-104.4 °C) Propellant Aerosol			
Flash back	No			
Flammability (HOC)	21.4159 kJ/g estimated			
Color	White.			
Boiling point	197.6 °F (92.2 °C) estimated			
ppearance Compressed liquefied gas.				

#### **Department of Transportation (DOT) Requirements**

• • • • •	-
Basic shipping requirements:	
Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG					
Basic shipping requirement	its:				
Proper shipping name	AEROSOI	LS			
Hazard class	2.1				
UN number	1950				
Additional information:					
Packaging exceptions	LTD QTY				
Item	5F				
Labels required	None				
Transport Category	2				
IATA	_				
Basic shipping requiremen		flammable			
Proper shipping name Hazard class	2.1	Inalianable			
UN number	1950				
Additional information:	1950				
Packaging exceptions	LTD QTY				
Labels required	2.1		2		
			V		
	15	i. Regulatory Information			
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. CERCLA/SARA Hazardous Substances - Not applicable.				
Occupational Safety and Health					
29 CFR 1910.1200 hazardo chemical		、 <i>,</i>			
CERCLA (Superfund) reportabl	e quantity				
None					
Superfund Amendments and R	eauthorization A	ct of 1986 (SARA)			
Hazard categories	Delayed H Fire Haza Pressure I	e Hazard - Yes lazard - Yes rd - Yes Hazard - Yes Hazard - No			
Section 302 extremely hazardous substance	No				
Section 311 hazardous che	mical Yes				
Inventory status					
Country(s) or region	Inventory nan	ne	On inventory (yes/no)*		
China	Inventory of Ex	kisting Chemical Substances in China (IECSC)	No		
Europe	European Inve	ntory of New and Existing Chemicals (EINECS)	No		
Europe	European List	of Notified Chemical Substances (ELINCS)	No		
Japan	Inventory of Ex	kisting and New Chemical Substances (ENCS)	No		
Korea	-	icals List (ECL)	No		
United States & Puerto Rico		ces Control Act (TSCA) Inventory	Yes		
	nents of this produc	t comply with the inventory requirements administered by	the governing country(s)		
State regulations					
U.S Pennsylvania - RTK (Rig		_			
n-Butane Odorless Mineral Spirits Propane	106-97-8 64742-48-9 74-98-6	Present Present Present			
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Present			

16. Other Information	
Further information	HMIS® is a registered trade and service mark of the NPCA.
HMIS® ratings	Health: 1* Flammability: 3 Physical hazard: 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
MSDS sections updated	This document has undergone significant changes and should be reviewed in its entirety.
Prepared by	Regulatory Compliance